

Durable, clean, quick to apply
and great to look at ...*

Silikal Reactive Resin Flooring for Production and Office Areas



Expect more from your floor.



** e.g. over night
or at the weekend*

Precision shapes and courageous colours

... steel chips and grinding agents can't bend a Silikal floor out of shape!

Shapes and colours go great together, and you can see the living proof of this at a manufacturer of metal moulds for shaping plastic products and accessories. The planner of this building placed special emphasis on good design from the ground up. In the production area, the offices and the entryway, the floors were made bright and colourful with a lively yellow coating of Silikal reactive resins.

This sunny yellow colour was chosen to offer a contrast to the company colours turquoise and blue which can be found on the outside and in the entrance hall. The colour also stands out beautifully

against the blue doors, window frames and beams, and gives the whole building a feeling of warmth and vitality.

There were not only good optical but also good acoustic reasons for this new floor. In the company's 500 m² production hall, where workers spend the entire day on their feet and a number of machines are running, the highly durable Silikal coating provides a cushion against noise. But that's not all: the softer surface also offers a cushion for tired feet and legs, not to mention the anti-skid properties for extra safety against slipping.

Proven in the field
For over 55 years
On many million m²



A piece of cake to put down—the floor is fully cured and ready for action after only 2 hours. A perfect way to avoid stand-stills in your operations!



Expect more from your floor.

Silikal GmbH

Reactive resins and polymer concrete for industrial floors and civil engineering projects

✉ Ostring 23

D-63533 Mainhausen

☎ +49 (0) 61 82 / 92 35 -0

☎ +49 (0) 61 82 / 92 35 -40

🌐 <http://www.silikal.de>

@ mail@silikal.de



Certified Quality Management System
Cert. Reg. No. 73 100 663



Certified Ecology Management System
Cert. Reg. No. 73 104 856

All details given above can only serve as general information. The various working conditions or circumstances beyond our control and the many different materials in use exclude any claim which might arise out of the information contained herein. In case of doubt, we recommend that you make sufficient trials on your own.